PAK-MAN SELF-CONTAINED COMPACTOR

PM6FS/PM6R

Pak-Man self-contained, leak-resistant compactors are ideal for small volume businesses.

The Pak-Man features a leak-resistant container, making it ideal for keeping waste contained – including wet waste. It features a space-maximizing design that's perfect for restaurants, nursing homes, retailers, and other small businesses. Compactors reduce overall waste disposal costs by reducing trash volume and hauling.



Value-Added Benefits

Space-maximizing design	 Designed for space-restricted areas Low 41" load height for ease of loading
Ideal for wet waste	Leak-resistant container is ideal for wet waste
Standard features included at no additional charge	 Key operated for added security External power unit with weather cover and 12'hoses NEMA 4 industrial control panel (U.S. & Canadian UL listed) Spring-loaded retainer teeth prevent spillage from spring-back Spring-assisted compactor lid is lightweight and easy to open Hydraulic quick-disconnect hose couplers Drain plug in container side
Ease of ownership	Purchase, rental, and leasing programs available
Warranty	1-1-1 warranty (1-year structural, 1-year parts, and 1-year labor)



PAK-MAN SELF-CONTAINED COMPACTOR

Specifications

Charge Box

Ram

Compactor Head

Electrical

Hydraulic

Performance

Front-Loading Pak-Man PM6FS

Wastequip rating Wastec rating

Clear top opening

Compactor weight

Ram penetration

Ram height

Face plate

Base plate

Top plate

Side plates

Breaker bar

Top deck (lid)

Electric motor

Voltage

Pump

Pump type

Hydraulic oil tank

Normal ram psi

Maximum ram psi

Cubic yard per hour

Power unit location

Cycle time

Cylinder bore/rod/stroke

Normal ram face pressure

Maximum ram face pressure

Power box

Automated cycle operation

Floor

Sides

80 15/16

PM6FS

1.17 cu. yds.

0.83 cu. yds.

2,150 lbs.

44 1/8"

12.5"

53" Length x 28" Width

44 1/8" Height x 53" Width

1/4" plate - 8 1/8" x 53"

1/4" plate - 6 5/8" x 44 1/4"

12 gauge - 17 1/8" x 53 1/4"

10 gauge - 41 1/2" x 47 1/2"

3" x 3" x 3/16" x 59 3/4"

208/230/460 Volt, 3 phase

Turn key switch-ram extends, retracts & stops automatically

3" bore, 1.5" rod, 16" stroke

21,229 psi at 1,500 psi

23,969 psi at 1,750 psi

UL rated, TEFC housing

12 gauge - 40" x 56"

3 HP

2.8 gpm

13 gallons

9.08 psi

10.25 psi

Remote

37 seconds

6 cu. yds.


114


Gear

3" x 3" x 3/16" ret. tube x 52 1/2"

PM6FS/PM6R

Rear-Loading Pak-Man PM6R





Features

Standard

- · Full container light
- 37 second cycle time
- Virtually dripless quick-disconnects
- Low temperature oil
- · Operational and service manual
- Primed and painted in multiple colors
- · Spring-loaded retainer teeth
- · Spring-assisted compactor lid with interlock
- · Drain plug in container side

Options

Oil heater



Replacement parts available online at www.wastebuilt.com

Standard Color Choices















Container Capacity



















301/3

60″op

PM6R*

2,270 lbs.



Colors shown are as accurate as printing allows. The actual color is subject to variation from the printed color sample. Color choices vary by plant location. Please contact your local sales representative for available colors. Custom colors are available upon request and are subject to an additional charge.

Tel: 877.468.9278 | sales@wastequip.com | www.wastequip.com