### STATIONARY COMPACTORS 350, 350HD and 350HDT

# 0.3 5/0<sup>-</sup> 20<sup>-</sup> 112<sup>--</sup> 12<sup>--</sup> 12<sup>--</sup>



Burgundy

Brown

| Specifica                | tions                            | 350                            | 350HD        | 350HDT                         |
|--------------------------|----------------------------------|--------------------------------|--------------|--------------------------------|
| Charge Box               | Wastequip rating                 | 3.5 cu. yds.                   |              |                                |
|                          | Wastec rating                    | 2.54 cu. yds.                  |              |                                |
|                          | Clear top opening                | 67″Lx 57″W                     |              |                                |
|                          | Compactor weight with power unit | 6,400 lbs.                     | 7,900 lbs.   | 8,490 lbs.                     |
| Ram                      | Ram height                       | 28″                            |              |                                |
|                          | Ram penetration                  | 18″                            |              |                                |
|                          | Face plate                       | 1/2"                           | 3/4″         |                                |
|                          | Base plate                       | 1/4″                           | 3/8″         |                                |
|                          | Top plate                        | 1/4″                           | 3/8″         |                                |
|                          | Side plates                      | 1/4″                           | 3/8"         |                                |
| Compactor<br>Head        | Floor                            | 1/2" AR plate                  |              | 3/4" AR plate                  |
|                          | Sides                            | 1/4" plate                     | 3/8" plate   |                                |
|                          | Breaker bar                      | 5" x 3" x 3" x 8" structural   |              |                                |
|                          |                                  | steel with 6" x 4" x 1/2" tube |              |                                |
|                          |                                  | stiffener                      |              |                                |
|                          | Top deck                         | 12 gauge                       |              |                                |
| Electrical               | Electric motor, fan cooled       | 15 hp                          |              |                                |
|                          | Voltage                          | 208/230/460, 3 phase<br>60 Hz  |              |                                |
|                          | Power box                        | UL rated, TEFC housing         |              |                                |
|                          | Automated cycle operation        | Turn-key switch, ram           |              |                                |
|                          |                                  | extends, retracts, and stops   |              |                                |
|                          |                                  | automatically                  |              |                                |
| Hydraulic<br>Performance | Pump                             | 13.0 gpm                       |              |                                |
|                          | Pump type                        | Regen                          |              |                                |
|                          | Hydraulic oil tank               | 39 gallon reservoir            |              |                                |
|                          | Cylinder bore/rod/stroke         | 6" bore, 4.5" rod, 90" stroke  |              | (2) 6" bore, 4.5" rod, 90"stro |
|                          | Normal ram face pressure         | 55,100 lbs.                    | 75,000 lbs.  |                                |
|                          | Maximum ram face pressure        | 63,600 lbs.                    | 86,500 lbs.  |                                |
|                          | Normal ram psi                   | 32.80 psi                      | 44.60 psi    |                                |
|                          | Maximum ram psi                  | 37.90 psi                      | 51.50 psi    |                                |
|                          | Cubic yard per hour              | 180                            | 132          | 90                             |
|                          | Power unit location              | External w/weather cover       |              |                                |
|                          | Cycle time                       | 51 seconds                     | 69.2 seconds | 101.7 seconds                  |

## White Gray Black Teal Med. Blue Dark Blue Med. Green Dark Green Cream Yellow Orange Red

Colors shown are as accurate as printing allows. The actual color is subject to variation from the printed color sample. Color choices vary by plant location. Please contact your local sales representative for available colors. Custom colors are available upon request and are subject to an

## WASTEQUIP<sup>®</sup>

#### Tel: 877.468.9278 | sales@wastequip.com | www.wastequip.com

Wastequip is the leading North American manufacturer of waste and recycling equipment for collecting, processing and transporting recyclables and solid or liquid waste. December 2016 © Wastequip, all rights reserved. Specifications subject to improvement without notice. Equipment displayed should be operated by properly trained personnel. Operators should become familiar with OSHA, ANSI and any other applicable standards or laws for using this equipment. Improper use, misuse, or lack of maintenance could cause injury to people and/or property. Photos used in the literature are illustrative only. We assume no liability or responsibility for proper training/operation of equipment not manufactured by Wastequip. We reserve the right to make changes at any time without notice. Information contained within this literature is intended to be the most accurate available at time of printing.

## STANDARD Features

#### • 1/2" AR Plate ram floor

- 51-second cycle time
- Heavy-duty breaker bar is 5" x 3" x 3/8" angled steel
- Full container light
- Low temperature oil
- Multi-cycle timer
- Operational / service manual
- NEMA 4 control panel protects against windblown dust, splashing water, and hose directed water
- Primed and painted in several colors

#### **Optional Features**

- Advance warning light
- Pressure gauge color coded
- Guide rails
- Oil heater
- Photo electric eye
- Odor control system
- Cart dumper
- Biodegradable oil
- Steel / Chutes / Hoppers

Wastebuilt Replacement available online

at www.wastebuilt.com

#### Standard Color Choices\*